

# EVDE25D4DUM

Delta DC Wallbox EV Charger 25kW Type CCS2 and CHAdeMO



|                       |                            |
|-----------------------|----------------------------|
| <b>Component type</b> | Charging device E-Mobility |
| <b>Range</b>          | DC Wallbox                 |
| <b>Model</b>          | N/A                        |
| <b>Product status</b> | Existing                   |



Durable, reliable, and commercial grade, the Delta range of DC chargers are strong and robust, ideal for fast charging in urban and rural environments. Air-cooled, steel cased with an IP55/IK10 rating, the Delta DC Charger range is capable in most weather and operating conditions. The Delta DC chargers also include an in-built modem; this enables the charger to connect to all third-party cloud-based platforms via its OCPP communication protocol. A truly robust EV charger for Australia and New Zealand's intense climate. Offering split load options, available with CCS2-CCS2 or CCS2-CHAdeMO plug combinations, the Delta DC Chargers will suit all current EV types.

|                       |   |               |
|-----------------------|---|---------------|
| <b>ELECTRICAL</b>     | Nominal connection power                | 25.0 kW       |
|                       | Max. power per charging point           | 25.0 kW       |
| <b>COMMUNICATION</b>  | With load management                    | Yes           |
|                       | With communication interface            | Yes           |
|                       | Function access control                 | Yes           |
| <b>CONSTRUCTION</b>   | Mounting method                         | Wall mounting |
|                       | Degree of protection (IP)               | IP55          |
|                       | Number of vehicle connectors Type 1     | 0             |
|                       | Number of vehicle connectors Type 1 CCS | 0             |
|                       | Number of vehicle connectors Type 2     | 0             |
|                       | Number of vehicle connectors Type 2 CCS | 1             |
|                       | Number of vehicle connectors CHAdeMO    | 1             |
| Emergency stop button | No                                      |               |
| <b>MECHANICAL</b>     | With display                            | Yes           |
|                       | Impact strength                         | IK10          |
| <b>DIMENSIONS</b>     | Height                                  | 430.0 mm      |
|                       | Depth                                   | 230.0 mm      |
|                       | Width                                   | 680.0 mm      |
|                       | Length of charging cable                | 4.0 m         |

# EVDE25D4DUM

Delta DC Wallbox EV Charger 25kW Type CCS2 and CHAdeMO



## RELATED PRODUCTS

### ACCESSORY

---



**Item No:** EVPEBKT02

**Required:** No

**Description:** Delta DC EV Charger 25kW Free Standing Mount Post